

Electronic Ballast For HID Lamps

220-240V



Approval Marks



Certified

EN 61347-1 : 2008
EN 61347-2-12 : 2005

Product Specification


Parameter	Conditions	Min	Nom	Max	Unit
Lamp Power	25°C, Nominal Input	-	20	-	W
Input Power	25°C, Nominal Input	-	24	-	W
Rated Input Voltage	25°C	220	230	240	V
AC Input Voltage Range with Tolerance For Safety	25°C	198	-	264	V
Input Frequency	25°C, Nominal Input	-	50-60	-	Hz
Input Current	25°C, Nominal Input	-	0.190	-	A
Power Factor	25°C, Nominal Input	0.52	0.55	0.58	-
Operating Frequency(Square Wave)	25°C, Nominal Input	-	120	-	Hz
Ignition Voltage	25°C, Nominal Input	-	3.00	4.00	KV
Withstand Voltage Test	1500V;1min	-	5	-	mA
Operating Ambient Temperature	Nominal Input	-15	-	+50	degC
Max Allowed Case Temperature	Nominal Input;Normal Conditions	-	-	+75	degC
Average Service Life	at 40°C ambient	50,000	-	-	hours
Failure Rate Per 1000h Operation	at 40°C ambient	-	-	0.20%	-
End - Of - Life Protection			Yes		
Automatic Shutdown In Case Of Lamp Failure			Yes		
Thermal Protection			Yes		

Lamp Type GE CMH 20W Lamp x 1

Application Space

Indoor Use
(Low Humidity, No Condensation)

Physical Parameter



L : 115.2 mm H : 28 mm
M : 105.6 mm K :
N : 30.4 mm R : 2.1 mm
W : 39.6 mm Slot On One Side Allowing Alignment : M+/-3 mm
Tolerance : $\geq 0 \sim 100 \geq +/0.5$ mm
 $100 \sim \geq +/1$ mm
Hard Wire : PRI : Screw type SEC: Screw type
Housing Material : Polycarbonate
Soldering : Lead-Free, Comply With RoHS
Label : Surface Print

Wiring Diagram

