


Electronic Ballast For HID Lamps

120-240V



Approval Marks



Product Specification

Parameter	Conditions	Min	Nom	Max	Unit
Lamp Power	25°C, Nominal Input	-	20	-	W
Input Power	25°C, Nominal Input	-	24	-	W
Rated Input Voltage	25°C	100	-	240	V
AC Input Voltage Range with Tolerance For Safety	25°C	90	-	264	V
Input Frequency	25°C	-	50-60	-	Hz
Input Current	25°C, Nominal Input	0.115	-	0.240	A
Power Factor	25°C, Nominal Input	-	0.95	-	-
Operating Frequency(Square Wave)	25°C, Nominal Input	-	120	-	Hz
Ignition Voltage	25°C, Nominal Input	-	3.50	5.00	KV
Withstand Voltage Test	1500V; 1min	-	5	-	mA
Operating Ambient Temperature	Nominal Input	-15	-	+55	degC
Max Allowed Case Temperature	55°C, Nominal Input	-	-	+75	degC
Average Service Life	at 40°C ambient	50,000	-	-	hours
Failure Rate Per 1000h Operation	at 40°C ambient	-	-	0.20%	-
End - Of - Life Protection			Yes		
Automatic Shutdown In Case Of Lamp Failure			Yes		
Thermal Protection			Yes		

Lamp Type HID 20W Lamp x 1


Application Space

Indoor Use

(Low Humidity, No Condensation)

Physical

Parameter



L : 143 mm H : 27.7 mm

M : 133 mm K :

N : 18.5 mm R : 3 mm

W : 86.7 mm

Tolerance : $\geq 0 \sim 100 \geq \pm 0.5$ mm
 $100 \sim \geq \pm 1$ mm

Terminal Block : Input : Plug-in Output : plug-in

Housing Material : Aluminium, Mylar Film

Soldering : Lead-Free, Comply With RoHS

Label : None

Wiring Diagram

